

A black and white photograph of a city at night. On the left, a tall, cylindrical skyscraper is illuminated with lights. In the center, a row of smaller buildings is lit up. On the right, a large bridge with a truss structure spans across a wide river. The lights from the buildings and bridge reflect on the water's surface. The sky is dark with some light clouds.

Stoned Bootkit

Peter Kleissner

Table of Contents

1. Introduction

1. About

2. Technical Overview

3. Windows Boot Environment

2. Stoned Architecture

1. Plugins

2. Boot Applications


3. Bootkit Installation & Usage

4. General Considerations

- **Independent Operating System Developer**
- **Professional Software Engineer and Malware Analyst**
- **Living in Wiener Neudorf, a suburb of Vienna (Austria)**

Introduction

- **Bootkit = Rootkit + Boot Capability**
Introduced by Vipin and Nitin Kumar
- **Stoned is a new bootkit targeting Windows operating systems**



Windows 2000
Windows XP
Windows Server 2003
Windows Vista
Windows Server 2008
Windows 7 RC
TrueCrypt


Main targets:

- Pwning all Windows versions from the boot
- Being able to bypass code integrity verifications & signed code checks

www.stoned-vienna.com

Architecture

Address	Size	Description
0000	440	Code Area
01B8	6	Microsoft Disk Signature
01BE	4*16	IBM Partition Table
01FE	2	Signature, 0AA55h
0200	-	Stoned Kernel Modules
-	-	Stoned Plugins
7A00	512	Backup of Original Bootloader
7C00	512	Configuration Area



Master Boot Record

File System

„A memory resident bootkit up to the Windows kernel“

+ Boot applications executed on startup

+ Drivers executed beside the Windows kernel

Stoned Virus

Your PC is now Stoned! (1987)

Your PC is now Stoned! ..again (2010)


Stoned is the name of a boot sector computer virus created in 1987, apparently in New Zealand. It was one of the very first viruses, and was, along with its many variants, very common and widespread in the early 1990s.

[http://en.wikipedia.org/wiki/Stoned \(computer virus\)](http://en.wikipedia.org/wiki/Stoned_(computer_virus))

Stoned was an OS independent boot sector infector.

- Probably the first bootkit?**
- 416 bytes of size, small & effective!**

Windows Boot Process



Ntldr = 16-bit stub + OS Loader (just binary appended)


Windows Vista splits up ntldr into bootmgr, winload.exe and winresume.exe

Windows XP	Windows Vista	Processor Environment
ntldr	bootmgr	Real Mode
OS Loader	OS Loader	Protected Mode
-	winload.exe	Protected Mode
NT kernel	NT kernel	Protected Mode + Paging

Insecuring Windows

Pwning Windows from the boot

Bootkit Real Mode	Relocates the code to the end of memory (4 KB), hooks interrupt 13h and patches code integrity verification
Bootkit Protected Mode	Patches image verification and hooks NT kernel
Kernel Code	NT kernel base address and PsLoadedModuleList are used for resolving own imports
Driver Code	Loads, relocates, resolves, executes all drivers in the list
PE Loader	PE-image relocation & resolving
Subsystem	Core functions for the Stoned Subsystem installed in Windows
Payload	Kernel drivers Applications using the subsystem




TrueCrypt Attack

There are two possible scenarios:

1. Only the system partition is encrypted
2. Full hard disk is encrypted

However, the master boot record always stays unencrypted.



A double forward for intercepting the encrypted and decrypted disk I/O.

Previous Bootkits

...	2006	2008	2010
		Mebroot	Stoned Bootkit
		BOOT KIT	TPMkit
Stoned	BootRoot	Vbootkit	Vbootkit 2.0

1987	2005	2007	2009
------	------	------	------

Previous research bootkits at conferences:

BootRoot	Windows XP	Black Hat USA 2005
Vbootkit	Windows Vista	Black Hat Europe 2007
Vbootkit 2.0	Windows 7 (x64)	Hack In The Box Dubai 2009

Stoned Architecture

Master Boot Record

Master Boot Record = first 63 sectors of hard disks; contains Partition Table and Bootloader

Modularized Stoned MBR contains:

Address	Size	Description	
0000	440	Code Area (Bootloader)	Bootloader.sys
01B8	6	Microsoft Disk Signature	
01BE	4*16	IBM Partition Table	
01FE	2	Signature, 0AA55h	
0200	2 KB	System Loader	System Loader.sys
0A00	1 KB	Textmode User Interface	Textmode TUI.sys
0E00	8 KB	Disk System	Disk System.sys
2E00	2 KB	Load Application Programming Interface for Real Mode	API [RM].sys
3600	512	Rescue Module	Rescue Module.sys
3800	8 KB	Free space (former User Interface and Hibernation File Attack)	[Embedded Boot Application]
5800	1.5 KB	Crypto Module	Crypto Module.sys
5E00	1 KB	Boot Module	Boot Module.sys
6200	4 KB	Pwn Windows	Windows.sys
7200	2 KB	Free Space	
Sector 61	512	Original Bootloader Backup	
Sector 62	512	Configuration Area / TrueCrypt volume-header information	

Stoned Modules

Management Modules:

Bootloader	System Loader	Plugin Manager
------------	---------------	----------------


API providing modules:

API [RM]	Boot Module	Crypto Module	Disk System
Locking Module	Rescue Module	Textmode UI	User Interface

Boot applications use the API provided by the modules.

They are independent from each other (this is also why the Windows pwning module can be injected into TrueCrypt's MBR).

Windows XP Boot




Ntldr contains a 16-bit stub and a 32 bit PE Image (= OS Loader)
This concept has not been changed in Windows until Windows Vista

Hooking & Patching (simplified):

- **Interrupt 13h hooked**
- **Ntldr hooked for calling 32-bit code and patching the code integrity verification**
- **Patching the NT kernel**
- **Executing payloads (driver)**

Windows Vista Boot



Hooking & Patching (simplified):

- Interrupt 13h hooked
- Bootmgr hooked to call 32-bit code
- Patching winload.exe code integrity verifications
- Patching the NT kernel

- **Currently only IBM-conform legacy boot supported**
- **In future EFI (Extensible Firmware Interface) support**

All common drives supported:

Floppy, CD, DVD, Blu-ray, USB flash drives, removable media, hard drives, network boot

➔ Media independent.

Plugins

Extending the core functionality by static bootkit attacks


User Interface	CO ₂ -Plugin	PE Infector	File Parsers
Hibernation File Attack	Pagefile Injector	Music Melody!	Boot Password Crack
AntiWPA	Persistent BIOS Infector	...and much more under development	

May be out sourced to the file system.

User data stored in CMOS memory?

Hibernation File Attack

- Predecessor of Stoned
- Static attack of bootkit
- Structures were revealed with BH USA 2008 „Windows Hibernation File for Fun and Profit“



The image shows two overlapping terminal windows from a QEMU virtual machine. The background window displays the 'Mount Boot Partitions...' step, showing the discovery and mounting of FAT and NTFS partitions, and a prompt to abort the hibernation file process. The foreground window displays the 'Open Hibernation Files...' step, showing the successful detection of a hibernation file, the extraction of a signature, the creation of a dump, and the successful modification of the image size.

```
QEMU
Mount Boot Partitions...
> found FAT Partition, mounting
> found NTFS Partition, mounting
Press any key to abort Hibernation File

QEMU
Open Hibernation Files...
> found hibernation file: Windows XP (active)
Signature found: PeterKleissnerTestString
Dump: Xpress Image (successful)
Debug: Create dump-file of found memory (successful) (successful)
* previous Image File Pointer: 00004000
Successful! New size: 00004609, old size: 00004FC0

Finished. Press F8 for Forensic Lockdown Software!
```

Save The Environment!

- **Example Plugin**
- **Throttling CPU speed down to 80%**
- **Normal user should not take any notice but our earth does :)**
- **Using the Advanced Configuration Programming Interface**

Boot Applications

Example: Sinowal Extractor

Using Stoned Bootkit to execute Sinowal and then extract the unpacked kernel driver

- **Tracing the memory by hooking the exports for `ExAllocatePool()` and `ExFreePool()` using the installed Stoned Subsystem**

→ Writing it out to disk for further analysis

- **New Anti-Malware technology?**

```
0007f720h: 50 4C 55 47 00 00 00 00 49 4E 46 4F 00 00 00 00 ; PLUG....INFO....
0007f730h: 42 49 50 00 2F 00 00 00 4E 4F 4F 50 00 00 00 00 ; BIP./...NOOP....
0007f740h: 55 4E 53 54 00 00 00 00 49 4E 53 54 00 00 00 00 ; UNST....INST....
0007f750h: 44 65 63 00 4E 6F 76 00 4F 63 74 00 53 65 70 00 ; Dec.Nov.Oct.Sep.
0007f760h: 41 75 67 00 4A 75 6C 00 4A 75 6E 00 4D 61 79 00 ; Aug.Jul.Jun.May.
0007f770h: 41 70 72 00 4D 61 72 00 46 65 62 00 4A 61 6E 00 ; Apr.Mar.Feb.Jan.
0007f780h: 53 61 74 00 46 72 69 00 54 68 75 00 57 65 64 00 ; Sat.Fri.Thu.Wed.
0007f790h: 54 75 65 00 4D 6F 6E 00 53 75 6E 00 0D 0A 00 00 ; Tue.Mon.Sun.....
0007f7a0h: 0D 0A 25 73 3A 20 00 00 25 78 00 00 63 68 75 6E ; ..%s: ..%x..chun
```

(Unpacked Sinowal kernel driver, here you see commands & domain name generation strings)

Bootkit Installation

Installation Guide

- 1. Backup original MBR**
- 2. Overwrite Master Boot Record**
- 3. Extract Files**

Problem: Raw sector access is required

Windows XP

Administrator rights

Windows Vista

Elevated Administrator rights

But every problem has its solution...

Raw Sector Access

▪ **Solution 1:**

75% of the users have full admin privileges

However, outside the enterprise and the Parental Controls case, most machines (75%) have a single account with full admin privileges.

According to Ben Fathi, Windows 7 User Account Control Engineer

▪ **Solution 2:**

Ask the system for elevated rights at runtime using `ShellExecute()` or request it via a manifest

If the user clicks "no" terrorize the user and ask again, e.g. start the elevated process until the user clicks "yes"

Elevated Administrator Rights

▪ Method 1: Application Manifest

```
<requestedPrivileges>  
  <requestedExecutionLevel level="asInvoker" uiAccess="true"/>  
</requestedPrivileges>
```

Application manifest (can be embedded into the application as resource)

```
/MANIFESTUAC:"level=asInvoker"
```

Visual Studio linker option to generate and include such a manifest

Level to be "asInvoker", "highestAvailable" or "requireAdministrator"

▪ Method 2: ShellExecute() at runtime

```
HINSTANCE ShellExecute(  
    HWND hwnd,  
    LPCTSTR lpOperation = "runas",  
    (...)  
);
```

MBR is still writable

- `CreateFile("\\.\PhysicalDrive0", ...)`
- Direct driver usage, IOCTLs
- Also works with Windows Vista and Server 2008:

A file system can write to a volume handle only if the following conditions are true:

Condition 1: The sectors that are being written to are boot sectors.

Condition 2: The sectors that are being written to reside outside the file system space.

According to the Microsoft Knowledgebase article #92448 "Changes to the file system and to the storage stack to restrict direct disk access and direct volume access in Windows Vista and in Windows Server 2008"

- 63 Sectors (31.5 KB size, sectors 0-62)

```
Administrator: C:\Windows\system32\cmd.exe
Microsoft Windows [Version 6.0.6001]
Copyright (c) 2006 Microsoft Corporation. All rights reserved.

C:\Users\Peter Kleissner>whoami
seattle\peter kleissner
```

**Time for a live
demonstration!**

General Considerations

- **Kernel Patch Protection**

 - Only for 64 bit and running systems

- **Digital Signatures**

 - We can inject unsigned code, no signed code check will be performed

- **Code integrity checks**

 - We do not patch executables on disk, therefore no integrity check will fail

- **Data Execution Prevention**

- **Same as in Vbootkit (BHE 2007)**

Thanks to my friends Vipin & Nitin Kumar!

- **Console Privilege Escalation**

- Changing privilege of every `cmd.exe` process to the same as `services.exe`
- Written as normal driver for Stoned

- **Displaying signature at startup**

Your PC is now Stoned! ..again

Developing with Stoned

- 1. Download the framework**
- 2. Write your own driver**
- 3. Modify the infector, or just:**

Use the installed Stoned Subsystem in Windows by your application

```
syscall, int 2Eh with
```

```
function numbers = 3000h-3FFFh
```

→ New open development platform

Secure the pre-boot Environment

Advice to OS vendors and HW architects:

Take use of the Trusted Platform Module and full volume encryption.

Full volume encryption software should:

- 1. Secure its own software**
- 2. Disable MBR overwrite in Windows**
- 3. Make MBR genuine verifications**

Do not try to fix software issues with security policies.

Future versions?

- **Linux support (OS independency)**
- **64-bit Windows support**
- **Defeating Trusted Platform Module**
- **Anti Windows Product Activation**

Black Hat Research Publications

www.blackhat.com

Sinowal / Mebroot

Vbootkit, Vipin & Nitin Kumar

www.nvllabs.in

**Stoned project, papers &
development framework**

www.stoned-vienna.com

Peter Kleissner at
Black Hat USA 2009

Thanks...

Questions?
Comments?

...for your attention!

Peter Kleissner at
Black Hat USA 2009

Thank You!